

## SRX-PRO 6.0 SOFTWARE



- Built to meet the client's needs, specifications, and budget with optional features and functions
- Supports up to 64 video channels per server
- Integrates with a wide range of ONVIF-compatible and other network cameras
- Optional dDisplay feature to project video onto external or spot monitor
- Optional Video Analytics, License Plate Recognition and POS integration
- Optional Cloud Managed Services (CMS)
- Controls up to 64 sensors/controls (inputs/outputs)

The SRX-Pro 6.0 is the i3 International's latest digital video management software. The enhanced features and functions of the SRX-Pro 6.0 will provide the best solution for the retail and commercial applications. SRX-Pro 6.0 software is ideal for network video recorders, while also supporting legacy analog cameras through compatible line of i3 HR16 analog video encoders. SRX-Pro 6.0 is flexible, adaptable, and user friendly and is uniquely designed to meet industry standards by integrating with multiple IP cameras, while utilizing i3's proprietary suite of video analytics to gather business intelligent data. i3 Annexus and other popular network cameras can be easily integrated with SRX-Pro through built-in camera search function. SRX-Pro software accepts a maximum of up to 64 network cameras (2MP) or a combination of up to 32 network cameras and 32 analog cameras (via HR16 encoder), or a similar combination based on customer's requirements and server hardware specifications.

SRX-Pro 6.0 integrates seamlessly with the i3 family of software and hardware products. The health status of multiple SRX-Pro servers can be monitored remotely through the Central Management Software (CMS). Optional video analytics suite empowers the users to gather business intelligent data such as customer traffic, traffic distribution and dwell times. Complementary application, CMS can then combine the traffic data gathered by the SRX-Pro video analytics module with the POS transaction data to generate a variety of additional business reports such as store score card, conversion rate, average sales and average customer traffic. Built to fulfill the traditional requirement, optional dDisplay feature integrates with SRX-Pro 6.0 to display live video on multiple external or spot monitors. When required, SRX-Pro 6.0 can integrate with the i3's UIO8 Power-over-Ethernet devices to control up to 64 inputs and 64 outputs.

SRX-Pro 6.0 is an adaptable software that can reside on a number of dedicated computer servers. Customer's needs, budget and installation requirements will dictate what features and functions are enabled on their SRX-Pro 6.0 software through purchased software license. Optional intelligent features such as PACDM®, LPR, Heatmap, iSearch and Video Analytics can be ordered at the time of purchase, or later.

Rev.180314

Where audio recording is required, SRX-Pro supports line level audio recording from i3 Annexus line of cameras. Recorded video and audio can be easily exported into a popular \*.mp4 format with the help of SRX-Pro easy-to-use backup wizard.

SRX-Pro 6.0 combines a user-friendly design with multi-level secure access of LDAP technology. The customer's IT department can ensure that LDAP users are given appropriate access to live and recorded video as well as Server setup and functions. The SRX-Pro 6.0 is accessible for remote viewing and search through Video Pilot Client, SRX-Pro Remote (legacy) and Smart Devices (iOS, Android). Moreover, because SRX-Pro 6.0 is a run-as-a-service application, the NVR can be easily made a part of the customer's domain policy. SRX-Pro 6.0 Service ensures that your security video continues recording uninterrupted after a system restart, without the need for user Windows OS login.

Currently, i3 International offers three Server chassis models, pre-installed with SRX-Pro software: U1 rackmount chassis with built-in PoE, and U2 and U3 chassis with built-in SATA bays. Users can also purchase SRX-Pro 6.0 software separately and use their own network video recorder server that meets or exceeds i3's minimum hardware requirements.

U1 and U1-L chassis supports up to 16 channels and 12TB, U2 supports up to 48 channels and 30TB and U3 chassis supports up to 64 channels and 80TB in JBOD video storage.

i3 International is rapidly gaining the reputation of a security industry leader for its powerful and cost-effective solution of an open platform IP video surveillance software that has multiple usages and is suitable for various industries.

For over 25 years, i3 has continually remained on the technological and innovation cutting edge of the security industry by providing an easy-to-use, yet powerful digital video management software. i3's innovative video analytics and POS integrations have given their end-users even more tools in order to protect their organizations' assets, while also allowing them to use video intelligently to drive profit.

#### VIDEO SERVER MODELS AVAILABLE WITH SRX-PRO 6.0

##### **Network Video Recorder:**

Ui. U1-L, U1-AL, U2, U3

i3 recommended computer server - please contact Technical Support for model numbers and specifications or visit our website:

<http://i3international.com/products/category/11>