May 1, 2015

## Re: Annexxus 68R/78R Release

To all of our customers and partners;

i3 International is pleased to announce the release of the new 360-degree Fisheye Infrared Camera series: Annexxus 68R (3MP) and Annexxus 78R (6MP).



In addition to the 360-degree view stream, these Megapixel cameras provide 3 simultaneous, independently-controlled digital pan-tilt-zoom (ePTZ) video streams, which may be recorded or viewed live. Multiple ePTZ streams allow each user to control the camera without interference from other users, as if it were their own unique PTZ.

The new i3 Fisheye camera series consists of two models: Ax68R – 3MP WDR Infrared Fisheye Camera Ax78R – 6MP Infrared Fisheye Camera (Digital WDR)

This line of cameras allows viewing video via standard web browser with no software required.

Users of SRX-Pro software will be able to view and control all four video streams in SRX-Pro Server, SRX-Pro Remote and Video Pilot Client. Only one IP license is required to support all four video streams.

The Ax68R/78R cameras have no moving parts, resulting in minimum wear and vastly reduced maintenance costs. Since this camera series comes with the full 360° field of view as well as high video resolution (3MP/6MP), a lot fewer Ax68R/78R cameras are required to cover any facility with minimal blind spots, as compared to more traditional PTZ fixed dome and bullet cameras. Perfect for both indoor and outdoor installations, the (digital) wide dynamic range function of this camera series helps achieve superb image quality with for even the most challenging environments.

Built-in microphone and speaker allow for the two-way audio communication between the SRX-Pro Server site and the camera installation site, while microSD support allows for "edge" video recording in case of the network failure.

## Benefits:

- Full hi-res (Up to to 2048\*2048/1536\*1536 resolution) 360° image stream for post-event analysis
- 3MP / 6MP image sensor
- Up to 15m IR range
- Wide area coverage with one camera, no blind spots, no moving parts, resulting in camera count and infrastructure reduction
- Total situational awareness, not achievable with fixed cameras and PTZ domes
- Three (3) live ePTZ video streams while simultaneously recording the full scene.
- Unsurpassable post-event analysis unavailable with traditional CCTV cameras
- Built-in microphone & speaker for 2-way audio on SRX-Pro Server
- MicroSD support for the "edge" video recording

Both camera models are backed by i3 International's superior 3-year limited camera warranty as well as i3's unparalleled 2-for-1 Camera Replacement program. Please read here to learn more about Two for One camera replacement program:

http://i3international.com/tools/media/medialibrary/PDF/Polices/limited\_product\_warranty.pdf

**i3 INTERNATIONAL TECHNICAL BULLETIN** 

Technical Bulletin # 150501-HW-01



The following modes of installation are possible: surface mount (ceiling/wall mount), wall-mount (with gooseneck bracket kit), pendant mount (with pendant mount kit), angle surface mount (with angle mount kit)

Bracket & Accessories:
DB13-14-547 – goose-neck bracket wall-mount kit
DB13-547 – pendant mount kit
DB78TSM – angle wall-/ceiling- mount kit

Please contact technical support if you have any questions or issues.

Email: support@i3international.com

Tel.: 1.877.877.7241

Live Chat: http://i3chat.i3international.com/chat

i3 International Inc.

Technical Support and Services

**i3 INTERNATIONAL TECHNICAL BULLETIN** 

Technical Bulletin # 150501-HW-01