



August 09, 2016

**Release Announcement:
Annexus Ax47R2, 1.3MP Mini Outdoor Infrared Dome.**

To all of our customers and partners;

i3 International is pleased to announce the release of the 1.3MP Outdoor IP Dome camera: Ax47R.

i3's Annexus Ax47R megapixel IP camera features 1.3MP video resolution and a 2.8mm F1.8 built-in lens.

This new camera series delivers triple streaming performance and supports H.264 and Motion JPEG video compression. H.264 codec allows for faster and more efficient video transmission over the network. This dome camera comes with digital Wide Dynamic Range (WDR), a feature that allows the cameras to adjust to varying outdoor lighting conditions and provides the best video quality despite the presence of high and low exposure areas in the camera's lens view. Annexus 47R cameras require PoE power and come with the Day/Night capability.

The Ax47R2 cameras are very versatile and offer many practical functions ideal for both indoor and outdoor application, such as Smart IR. Smart IR technology achieves superior images in low-light conditions by automatic LED brightness adjustment depending on the object's distance from the camera. These moisture-, dust- and vandal-resistant cameras are IP67-certified and IK10-compliant and come in an aluminum casing, which makes them suitable for outdoor conditions, while also being perfect for the indoor installations. Corridor view is available for users that would like to view a hallway or a single store aisle.

The versatility of Ax47R IP cameras makes them suitable for a range of video surveillance applications, including government and industrial buildings, retail environments, airports, railway stations and schools. These series are suited for use with the i3's NVR and HVR - Video Management Systems.

Ax47R2 camera series is backed by i3 International's superior 3-year limited camera warranty as well as i3's unparalleled 2-for-1 Camera Replacement program. Please read here to learn more about Two-for-One camera replacement program:

http://i3international.com/tools/media/medialibrary/PDF/Polices/limited_product_warranty.pdf

The following modes of installation are possible: surface-mounting, surface mounting with Ax61BB back box (not included), wall-mounting w/goose-neck bracket (not included), and pendant pole mounting.

Brackets & Accessories:

Ax61BB – back box

DB60 – goose-neck bracket wall-mount kit

DB60CPM – corner / pole mount kit (used in conjunction with DB60)

Please contact technical support if you have any questions or issues.

Email: support@i3international.com

Tel.: 1.877.877.7241

Live Chat: <http://i3chat.i3international.com/chat>

i3 International Inc.
Technical Support and Services

