



May 1, 2015

Re: SRX-Pro v.3.3.2 Release Notice

To all of our customers and partners;

i3 International is pleased to announce the external release of the SRX-Pro Server and Remote v3.3.2. The production release is scheduled for **June 1, 2015**. *All units* built from that date forward will be built with SRX-Pro v3.3.2 unless the customer or integrator requests otherwise in writing.

Note that Special Build routings will remain unchanged and will follow previously approved specifications. In order to move the Special Built routing to the new SRX-Pro v3.3.2 software release, the integrator/end user must indicate so in writing.

Following i3's standards of backward compatibility, all customers using SRX-Pro Remote and Video Pilot Client (VPC) software will be expected to upgrade to v3.3.2 in order to continue being able to connect to their remote sites running SRX-Pro Server v3.3.2.XX. To help with the update, built-in auto upgrade function can be used in the VPC application. Upon the VPC startup, the automatic check for new version releases will be performed and the user will be prompted to authorize the upgrade (Internet connection required).

The latest SRX-Pro Server, SRX-Pro Remote and Video Pilot Client versions are available for download from the i3 website: <http://i3international.com/index.php/software-downloads>

New Features and Functions:

- i3-WDT (Watchdog Timer) board support.
See [150429-HW-01 \(New Pricelist Product Line changes\).pdf](#) bulletin for more details.
- 2-way audio support for Annexus68 and Annexus78 IP cameras. Communicate with the camera installation site from the SRX-Pro Server. Received and sent audio can be recorded together with the video. Note, feature not supported by SRX-Pro Remote. See [150501-HW-01 \(Annexus 68R/78R Release\).pdf](#) bulletin for more details.

Improvements:

- Monitor settings are saved, even after the monitor is disconnected. When the same monitor is re-connected, display settings do not need to be re-configured.
- Video Analytics database has been re-located to D:\ partition.
Note, factory default D:\ partition size has been increased to 100GB.
- SRX-Pro Remote Display Monitor / Camera resolution mismatch reconciliation. If the camera resolution exceeds that of the VGA card used, camera resolution will be scaled down for proper display.
Note, applies to SRX-Pro Remote only.
- Single text overlay area support by default. Second area can be drawn on demand. When only one text area is drawn on the screen, it is always assigned ID 1.
- ONVIF adapter has been updated to support Canon and Panasonic cameras
- Video Analytics uses Live Mode current video stream for detection.
- Hardware Watchdog timer increased to 6 minutes

Further Improvements:

- Mobile Remote App shows all cameras when Video Analytics is enabled on SRX-Pro Server
- SRX-Pro Remote software viewing continuity improvement.
- Windows "Medium - 125%" or "Larger - 150%" DPI setting supported on SRX-Pro Remote software.
- OCX improvement.
- SRX-Pro Remote approved and tested for Citrix environment.

Please consult with your Regional Sale Managers for more information.
Thank you very much for your attention and cooperation.

Please contact technical support if you have any questions or issues.

Email: support@i3international.com

Tel.: 1.877.877.7241

Live Chat: <http://i3chat.i3international.com/chat>

i3 International Inc.

Technical Support and Services